

COMPONENTS, MATERIALS & FINISHES

LEGS in Ø25x2mm cold-rolled steel tube. SEAT in Ø25x2mm cold-rolled steel tube chassis, covered with perforated steel sheet of 2mm thickness. Standard perforated (Flowers) or basic perforated (Basic). Steel tubular legs and perforated steel sheets for seating, covered in cataphoresis and painted with polyester resin without TGIC in a corten colour or silver grey (RAL9006) microtexturized. Both colours are metalized. M-8 stainless steel SCREWS with safety nut.

DIMENSIONS & WEIGHTS

The Poet: $180 \times 84 \times H.74$ cm (H. Seat: 41cm) / 36Kg

70.9" x 33.1" x H.29.1"(H. Seat: 16.1") / 79.4 lbs The placement of the screw for assembling is $\emptyset 8$ mm.

INSTALLATION

The benches must always be properly screwed to the floor. Screws are not supplied by BD.

PACKAGING

The legs and seats are delivered packaged on pallets, protected by cardboard and plastic corner guards.

The benches will be supplied unassembled.


TESTS

The benches are certified based on the UNE-EN standard 12727:01 FURNITURE. ALIGNED SEATS, in 4 level, severe public use. The horizontal tables based on the ISO/DIS standard 8019:86 "TABLES. RESISTANCE AND DURABILITY", in 5 level, severe public use. Salt spray corrosion tests (500 hours) for the painting process.


CLEANING & MAINTENANCE

The bench should be cleaned with a damp cloth or a mild soap, recommended to use green baize. Do not use cleaning products

STANDARD POET







BASIC POET

