

ZIRKOL – O

ZIRKOL -O is a family of oval suspension lamps suitable for general and decorative lighting.

Anodized aluminium body and opal screen for a homogeneous lighting.

Available as single direct light emission version or with double light emission with high flux and different colour temperatures.

Remote driver and dimmer interface included



2X1M | DOWNLIGHT - 2700K

LAMPING

Source	Linear LED
Total power	74W
Emission	Diffused orientable
Switching	DALI 1-100%
Tension	110/240V
Color temperature	2700K
Luminous flux	4282lm
Typ CRI	90
Energy class	A+
IP class	40
Dimensions	200x100x5cm
Materials	Aluminium
Notes	included: 1 driver WALIMLED100/24, 1 dimmer interface WDIMDALIHP, 1x electrical cable 5m, 4x adjustable metal cables length 3m (including ceiling attachment). Shipped assembled
Customization options	Shapes, sizes
Accessories	Canopy, for concrete ceiling Canopy box, 1 driver, 1 electrical cable Ceiling plate, for false ceiling
Net lamp weight	6 kg

Codes

BZRO16A20G15DBO
BZRO16A20G15DNE
BZRO16A20G15DOR


Structure

white
black
gold

PACKAGE

Package 01 Dimension: 210x110x15 cm / Gross weight: 11,4 kg

Certificazioni



2X1M | UP - DOWNLIGHT -2700K

LAMPING

Source	Linear LED
Total power	148W
Emission	Diffused orientable
Switching	DALI 1-100%
Tension	220/240V
Color temperature	2700K
Luminous flux	8563lm
Typ CRI	90
Energy class	A+
IP class	40
Dimensions	200x100x5cm
Materials	Aluminium
Notes	included: 1 driver WALIM150W24VIN, 1 dimmer interface WDIMDALIHP, 2x electrical cables 5m, 4x adjustable metal cables length 3m (including ceiling attachment). Shipped assembled
Customization options	Shapes, sizes
Accessories	Canopy, for concrete ceiling Canopy box, 1 driver, 2 electrical cables Ceiling plate, for false ceiling
Net lamp weight	6,1 kg

Codes

BZRO17A20G15DBO
BZRO17A20G15DNE
BZRO17A20G15DOR


Structure

white
black
gold

PACKAGE

Package 01 Dimension: 210x110x15 cm / Gross weight: 11,5 kg

Certificazioni



2X1M | DOWNLIGHT - 3000K

LAMPING

Source	Linear LED
Total power	74W
Emission	Diffused orientable
Switching	DALI 1-100%
Tension	110/240V
Color temperature	3000K
Luminous flux	4533lm
Typ CRI	90
Energy class	A+
IP class	40
Dimensions	200x100x5cm
Materials	Aluminium
Notes	included: 1 driver WALIMLED100/24, 1 dimmer interface WDIMDALIHP, 1x electrical cable 5m, 4x adjustable metal cables length 3m (including ceiling attachment). Shipped assembled
Customization options	Shapes, sizes
Accessories	Canopy, for concrete ceiling Canopy box, 1 driver, 1 electrical cable Ceiling plate, for false ceiling
Net lamp weight	6 kg

Codes

BZRO16A20G15WBO
BZRO16A20G15WNE
BZRO16A20G15WOR


Structure

white
black
gold

PACKAGE

Package 01 Dimension: 210x110x15 cm / Gross weight: 11,4 kg

Certificazioni



2X1M | UP - DOWNLIGHT - 3000K

LAMPING

Source	Linear LED
Total power	148W
Emission	Diffused orientable
Switching	DALI 1-100%
Tension	220/240V
Color temperature	3000K
Luminous flux	9067lm
Typ CRI	90
Energy class	A+
IP class	40
Dimensions	200x100x5cm
Materials	Aluminium
Notes	included: 1 driver WALIM150W24VIN, 1 dimmer interface WDIMDALIHP, 2x electrical cables 5m, 4x adjustable metal cables length 3m (including ceiling attachment). Shipped assembled
Customization options	Shapes, sizes
Accessories	Canopy, for concrete ceiling Canopy box, 1 driver, 2 electrical cables Ceiling plate, for false ceiling
Net lamp weight	6,1 kg

Codes

BZRO17A20G15WBO
BZRO17A20G15WNE
BZRO17A20G15WOR


Structure

white
black
gold

PACKAGE

Package 01 Dimension: 210x110x15 cm / Gross weight: 11,5 kg

Certificazioni



2X1M | DOWNLIGHT - 4000K

LAMPING

Source	Linear LED
Total power	74W
Emission	Diffused orientable
Switching	DALI 1-100%
Tension	110/240V
Color temperature	4000K
Luminous flux	5037lm
Typ CRI	90
Energy class	A+
IP class	40
Dimensions	200x100x5cm
Materials	Aluminium
Notes	included: 1 driver WALIMLED100/24, 1 dimmer interface WDIMDALIHP, 1x electrical cable 5m, 4x adjustable metal cables length 3m (including ceiling attachment). Shipped assembled
Customization options	Shapes, sizes
Accessories	Canopy, for concrete ceiling Canopy box, 1 driver, 1 electrical cable Ceiling plate, for false ceiling
Net lamp weight	6 kg

Codes

BZRO16A20G15NBO
BZRO16A20G15NNE
BZRO16A20G15NOR


Structure

white
black
gold

PACKAGE

Package 01 Dimension: 210x110x15 cm / Gross weight: 11,4 kg

Certificazioni



2X1M | UP - DOWNLIGHT - 4000K

LAMPING

Source	Linear LED
Total power	148W
Emission	Diffused orientable
Switching	DALI 1-100%
Tension	220/240V
Color temperature	4000K
Luminous flux	10074lm
Typ CRI	90
Energy class	A+
IP class	40
Dimensions	200x100x5cm
Materials	Aluminium
Notes	included: 1 driver WALIM150W24VIN, 1 dimmer interface WDIMDALIHP, 2x electrical cables 5m, 4x adjustable metal cables length 3m (including ceiling attachment). Shipped assembled
Customization options	Shapes, sizes
Accessories	Canopy, for concrete ceiling Canopy box, 1 driver, 2 electrical cables Ceiling plate, for false ceiling
Net lamp weight	6,1 kg

Codes

BZRO17A20G15NBO
BZRO17A20G15NNE
BZRO17A20G15NOR


Structure

white
black
gold

PACKAGE

Package 01 Dimension: 210x110x15 cm / Gross weight: 11,5 kg

Certificazioni



3X1M | DOWNLIGHT - 2700K

LAMPING

Source	Linear LED
Total power	103W
Emission	Diffused orientable
Switching	DALI 1-100%
Tension	220/240V
Color temperature	2700K
Luminous flux	5948lm
Typ CRI	90
Energy class	A+
IP class	40
Dimensions	300x100x5cm
Materials	Aluminium
Notes	included: 1 driver WALIM150W24VIN, 1 dimmer interface WDIMDALIHP, 1x electrical cable 5m, 4x adjustable metal cables length 3m (including ceiling attachment). Shipped assembled
Customization options	Shapes, sizes
Accessories	Canopy, for concrete ceiling Canopy box, 1 driver, 1 electrical cable Ceiling plate, for false ceiling
Net lamp weight	7,7 kg


Codes
BZRO16A30G15DBO
BZRO16A30G15DNE
BZRO16A30G15DOR

Structure
white
black
gold

PACKAGE

Package 01 Dimension: 310x100x15 cm / Gross weight: 15,7 kg

Certificazioni



3X1M | UP - DOWNLIGHT - 2700K

LAMPING

Source	Linear LED
Total power	206W
Emission	Diffused orientable
Switching	DALI 1-100%
Tension	220/240V
Color temperature	2700K
Luminous flux	11895lm
Typ CRI	90
Energy class	A+
IP class	40
Dimensions	300x100x5cm
Materials	Aluminium
Notes	included: 1 driver WALIM250W24VIN, 1 dimmer interface WDIMDALIHP, 2x electrical cables 5m, 4x adjustable metal cables length 3m (including ceiling attachment). Shipped assembled
Customization options	Shapes, sizes
Accessories	Canopy, for concrete ceiling Canopy box, 1 driver, 2 electrical cables Ceiling plate, for false ceiling
Net lamp weight	8 kg


Codes
BZRO17A30G15DBO
BZRO17A30G15DNE
BZRO17A30G15DOR

Structure
white
black
gold

PACKAGE

Package 01 Dimension: 310x100x15 cm / Gross weight: 16 kg

Certificazioni



3X1M | DOWNLIGHT - 3000K

LAMPING

Source	Linear LED
Total power	103W
Emission	Diffused orientable
Switching	DALI 1-100%
Tension	220/240V
Color temperature	3000K
Luminous flux	6297lm
Typ CRI	90
Energy class	A+
IP class	40
Dimensions	300x100x5cm
Materials	Aluminium
Notes	included: 1 driver WALIM150W24VIN, 1 dimmer interface WDIMDALIHP, 1x electrical cable 5m, 4x adjustable metal cables length 3m (including ceiling attachment). Shipped assembled
Customization options	Shapes, sizes
Accessories	Canopy, for concrete ceiling Canopy box, 1 driver, 1 electrical cable Ceiling plate, for false ceiling
Net lamp weight	7,7 kg

Codes

BZRO16A30G15WBO
BZRO16A30G15WNE
BZRO16A30G15WOR


Structure

white
black
gold

PACKAGE

Package 01 Dimension: 310x100x15 cm / Gross weight: 15,7 kg

Certificazioni



3X1M | UP - DOWNLIGHT - 3000K

LAMPING

Source	Linear LED
Total power	206W
Emission	Diffused orientable
Switching	DALI 1-100%
Tension	220/240V
Color temperature	3000K
Luminous flux	12595lm
Typ CRI	90
Energy class	A+
IP class	40
Dimensions	300x100x5cm
Materials	Aluminium
Notes	included: 1 driver WALIM250W24VIN, 1 dimmer interface WDIMDALIHP, 2x electrical cables 5m, 4x adjustable metal cables length 3m (including ceiling attachment). Shipped assembled
Customization options	Shapes, sizes
Accessories	Canopy, for concrete ceiling Canopy box, 1 driver, 2 electrical cables Ceiling plate, for false ceiling
Net lamp weight	8 kg

Codes

BZRO17A30G15WBO
BZRO17A30G15WNE
BZRO17A30G15WOR


Structure

white
black
gold

PACKAGE

Package 01 Dimension: 310x100x15 cm / Gross weight: 16 kg

Certificazioni



3X1M | DOWNLIGHT - 4000K

LAMPING

Source	Linear LED
Total power	103W
Emission	Diffused orientable
Switching	DALI 1-100%
Tension	220/240V
Color temperature	4000K
Luminous flux	6997lm
Typ CRI	90
Energy class	A+
IP class	40
Dimensions	300x100x5cm
Materials	Aluminium
Notes	included: 1 driver WALIM150W24VIN, 1 dimmer interface WDIMDALIHP, 1x electrical cable 5m, 4x adjustable metal cables length 3m (including ceiling attachment). Shipped assembled
Customization options	Shapes, sizes
Accessories	Canopy, for concrete ceiling Canopy box, 1 driver, 1 electrical cable Ceiling plate, for false ceiling
Net lamp weight	7,7 kg

Codes

BZRO16A30G15NBO
BZRO16A30G15NNE
BZRO16A30G15NOR


Structure

white
black
gold

PACKAGE

Package 01 Dimension: 310x100x15 cm / Gross weight: 15,7 kg

Certificazioni



3X1M | UP - DOWNLIGHT - 4000K

LAMPING

Source	Linear LED
Total power	206W
Emission	Diffused orientable
Switching	DALI 1-100%
Tension	220/240V
Color temperature	4000K
Luminous flux	13994lm
Typ CRI	90
Energy class	A+
IP class	40
Dimensions	300x100x5cm
Materials	Aluminium
Notes	included: 1 driver WALIM250W24VIN, 1 dimmer interface WDIMDALIHP, 2x electrical cables 5m, 4x adjustable metal cables length 3m (including ceiling attachment). Shipped assembled
Customization options	Shapes, sizes
Accessories	Canopy, for concrete ceiling Canopy box, 1 driver, 2 electrical cables Ceiling plate, for false ceiling
Net lamp weight	8 kg


Codes
BZRO17A30G15NBO
BZRO17A30G15NNE
BZRO17A30G15NOR

Structure
white
black
gold

PACKAGE

Package 01 Dimension: 310x100x15 cm / Gross weight: 16 kg

Certificazioni



2,5X1,5M | DOWNLIGHT - 2700K

LAMPING

Source	Linear LED
Total power	97W
Emission	Diffused orientable
Switching	DALI 1-100%
Tension	220/240V
Color temperature	2700K
Luminous flux	5589lm
Typ CRI	90
Energy class	A+
IP class	40
Dimensions	250x150x5cm
Materials	Aluminium
Notes	included: 1 driver WALIM150W24VIN, 1 dimmer interface WDIMDALIHP, 1x electrical cable 5m, 6x adjustable metal cables length 3m (including ceiling attachment). Shipped in 4 pieces
Customization options	Shapes, sizes
Accessories	Canopy, for concrete ceiling Canopy box, 1 driver, 1 electrical cable Ceiling plate, for false ceiling
Net lamp weight	7,3 kg

Codes

BZRO16B25G15DBO
BZRO16B25G15DNE
BZRO16B25G15DOR


Structure

white
black
gold

PACKAGE

Package 01 Dimension: 160x160x15 cm / Gross weight: 10,8 kg

Certificazioni



2,5X1,5M | UP - DOWNLIGHT - 2700K

LAMPING

Source	Linear LED
Total power	193W
Emission	Diffused orientable
Switching	DALI 1-100%
Tension	220/240V
Color temperature	2700K
Luminous flux	11179lm
Typ CRI	90
Energy class	A+
IP class	40
Dimensions	250x150x5cm
Materials	Aluminium
Notes	included: 1 driver WALIM250W24VIN, 1 dimmer interface WDIMDALIHP, 4x electrical cables 5m, 6x adjustable metal cables length 3m (including ceiling attachment). Shipped in 4 pieces
Customization options	Shapes, sizes
Accessories	Canopy, for concrete ceiling Ceiling plate, for false ceiling
Net lamp weight	8,1 kg

Codes

BZRO17B25G15DBO
BZRO17B25G15DNE
BZRO17B25G15DOR


Structure

white
black
gold

PACKAGE

Package 01 Dimension: 160x160x15 cm / Gross weight: 11,6 kg

Certificazioni



2,5X1,5M | DOWNLIGHT - 3000K

LAMPING

Source	Linear LED
Total power	97W
Emission	Diffused orientable
Switching	DALI 1-100%
Tension	220/240V
Color temperature	3000K
Luminous flux	5918lm
Typ CRI	90
Energy class	A+
IP class	40
Dimensions	250x150x5cm
Materials	Aluminium
Notes	included: 1 driver WALIM150W24VIN, 1 dimmer interface WDIMDALIHP, 1x electrical cable 5m, 6x adjustable metal cables length 3m (including ceiling attachment). Shipped in 4 pieces
Customization options	Shapes, sizes
Accessories	Canopy, for concrete ceiling Canopy box, 1 driver, 1 electrical cable Ceiling plate, for false ceiling
Net lamp weight	7,3 kg

Codes

BZRO16B25G15WBO
BZRO16B25G15WNE
BZRO16B25G15WOR


Structure

white
black
gold

PACKAGE

Package 01 Dimension: 160x160x15 cm / Gross weight: 10,8 kg

Certificazioni



2,5X1,5M | UP - DOWNLIGHT - 3000K

LAMPING

Source	Linear LED
Total power	193W
Emission	Diffused orientable
Switching	DALI 1-100%
Tension	220/240V
Color temperature	3000K
Luminous flux	11836lm
Typ CRI	90
Energy class	A+
IP class	40
Dimensions	250x150x5cm
Materials	Aluminium
Notes	included: 1 driver WALIM250W24VIN, 1 dimmer interface WDIMDALIHP, 4x electrical cables 5m, 6x adjustable metal cables length 3m (including ceiling attachment). Shipped in 4 pieces
Customization options	Shapes, sizes
Accessories	Canopy, for concrete ceiling Ceiling plate, for false ceiling
Net lamp weight	8,1 kg

Codes

BZRO17B25G15WBO
BZRO17B25G15WNE
BZRO17B25G15WOR


Structure

white
black
gold

PACKAGE

Package 01 Dimension: 160x160x15 cm / Gross weight: 11,6 kg

Certificazioni



2,5X1,5M | DOWNLIGHT - 4000K

LAMPING

Source	Linear LED
Total power	97W
Emission	Diffused orientable
Switching	DALI 1-100%
Tension	220/240V
Color temperature	4000K
Luminous flux	6576lm
Typ CRI	90
Energy class	A+
IP class	40
Dimensions	250x150x5cm
Materials	Aluminium
Notes	included: 1 driver WALIM150W24VIN, 1 dimmer interface WDIMDALIHP, 1x electrical cable 5m, 6x adjustable metal cables length 3m (including ceiling attachment). Shipped in 4 pieces
Customization options	Shapes, sizes
Accessories	Canopy, for concrete ceiling Canopy box, 1 driver, 1 electrical cable Ceiling plate, for false ceiling
Net lamp weight	7,3 kg

Codes

BZRO16B25G15NBO
BZRO16B25G15NNE
BZRO16B25G15NOR


Structure

white
black
gold

PACKAGE

Package 01 Dimension: 160x160x15 cm / Gross weight: 10,8 kg

Certificazioni



2,5X1,5M | UP - DOWNLIGHT - 4000K

LAMPING

Source	Linear LED
Total power	193W
Emission	Diffused orientable
Switching	DALI 1-100%
Tension	220/240V
Color temperature	4000K
Luminous flux	13152lm
Typ CRI	90
Energy class	A+
IP class	40
Dimensions	250x150x5cm
Materials	Aluminium
Notes	included: 1 driver WALIM250W24VIN, 1 dimmer interface WDIMDALIHP, 4x electrical cables 5m, 6x adjustable metal cables length 3m (including ceiling attachment). Shipped in 4 pieces
Customization options	Shapes, sizes
Accessories	Canopy, for concrete ceiling Ceiling plate, for false ceiling
Net lamp weight	8,1 kg

Codes

BZRO17B25G15NBO
BZRO17B25G15NNE
BZRO17B25G15NOR


Structure

white
black
gold

PACKAGE

Package 01 Dimension: 160x160x15 cm / Gross weight: 11,6 kg

Certificazioni



3,5X1,5M | DOWNLIGHT - 2700K

LAMPING

Source	Linear LED
Total power	125W
Emission	Diffused orientable
Switching	DALI 1-100%
Tension	220/240V
Color temperature	2700K
Luminous flux	7255lm
Typ CRI	90
Energy class	A+
IP class	40
Dimensions	350x150x5cm
Materials	Aluminium
Notes	included: 1 driver WALIM150W24VIN, 1 dimmer interface WDIMDALIHP, 1x electrical cable 5m, 6x adjustable metal cables length 3m (including ceiling attachment). Shipped in 4 pieces
Customization options	Shapes, sizes
Accessories	Canopy, for concrete ceiling Canopy box, 1 driver, 1 electrical cable Ceiling plate, for false ceiling
Net lamp weight	9,1 kg

Codes

BZRO16B35G15DBO
BZRO16B35G15DNE
BZRO16B35G15DOR


Structure

white
black
gold

PACKAGE

Package 01 Dimension: 210x110x15 cm / Gross weight: 14,5 kg

Certificazioni



3,5X1,5M | UP - DOWNLIGHT - 2700K

LAMPING

Source	Linear LED
Total power	251W
Emission	Diffused orientable
Switching	DALI 1-100%
Tension	220/240V
Color temperature	2700K
Luminous flux	1451lm
Typ CRI	90
Energy class	A+
IP class	40
Dimensions	350x150x5cm
Materials	Aluminium
Notes	included: 2 drivers WALIM150W24VIN, 2x dimmer interface WDIMDALIHP, 4x electrical cables 5m, 6x adjustable metal cables length 3m (including ceiling attachment). Shipped in 4 pieces
Customization options	Shapes, sizes
Accessories	Canopy, for concrete ceiling Ceiling plate, for false ceiling
Net lamp weight	9,9 kg

Codes

BZRO17B35G15DBO
BZRO17B35G15DNE
BZRO17B35G15DOR


Structure

white
black
gold

PACKAGE

Package 01 Dimension: 210x110x15 cm / Gross weight: 15,3 kg

Certificazioni



3,5X1,5M | DOWNLIGHT - 3000K

LAMPING

Source	Linear LED
Total power	125W
Emission	Diffused orientable
Switching	DALI 1-100%
Tension	220/240V
Color temperature	3000K
Luminous flux	7682lm
Typ CRI	90
Energy class	A+
IP class	40
Dimensions	350x150x5cm
Materials	Aluminium
Notes	included: 1 driver WALIM150W24VIN, 1 dimmer interface WDIMDALIHP, 1x electrical cable 5m, 6x adjustable metal cables length 3m (including ceiling attachment). Shipped in 4 pieces
Customization options	Shapes, sizes
Accessories	Canopy, for concrete ceiling Canopy box, 1 driver, 1 electrical cable Ceiling plate, for false ceiling
Net lamp weight	9,1 kg

Codes

BZRO16B35G15WBO
BZRO16B35G15WNE
BZRO16B35G15WOR


Structure

white
black
gold

PACKAGE

Package 01 Dimension: 210x110x15 cm / Gross weight: 14,5 kg

Certificazioni



3,5X1,5M | UP - DOWNLIGHT - 3000K

LAMPING

Source	Linear LED
Total power	251W
Emission	Diffused orientable
Switching	DALI 1-100%
Tension	220/240V
Color temperature	3000K
Luminous flux	15364lm
Typ CRI	90
Energy class	A+
IP class	40
Dimensions	350x150x5cm
Materials	Aluminium
Notes	included: 2 drivers WALIM150W24VIN, 2x dimmer interface WDIMDALIHP, 4x electrical cables 5m, 6x adjustable metal cables length 3m (including ceiling attachment). Shipped in 4 pieces
Customization options	Shapes, sizes
Accessories	Canopy, for concrete ceiling Ceiling plate, for false ceiling
Net lamp weight	9,9 kg

Codes

BZRO17B35G15WBO
BZRO17B35G15WNE
BZRO17B35G15WOR


Structure

white
black
gold

PACKAGE

Package 01 Dimension: 210x110x15 cm / Gross weight: 15,3 kg

Certificazioni



3,5X1,5M | DOWNLIGHT - 4000K

LAMPING

Source	Linear LED
Total power	125W
Emission	Diffused orientable
Switching	DALI 1-100%
Tension	220/240V
Color temperature	4000K
Luminous flux	8536lm
Typ CRI	90
Energy class	A+
IP class	40
Dimensions	350x150x5cm
Materials	Aluminium
Notes	included: 1 driver WALIM150W24VIN, 1 dimmer interface WDIMDALIHP, 1x electrical cable 5m, 6x adjustable metal cables length 3m (including ceiling attachment). Shipped in 4 pieces
Customization options	Shapes, sizes
Accessories	Canopy, for concrete ceiling Canopy box, 1 driver, 1 electrical cable Ceiling plate, for false ceiling
Net lamp weight	9,1 kg

Codes

BZRO16B35G15NBO
BZRO16B35G15NNE
BZRO16B35G15NOR


Structure

white
black
gold

PACKAGE

Package 01 Dimension: 210x110x15 cm / Gross weight: 14,5 kg

Certificazioni



3,5X1,5M | UP - DOWNLIGHT - 4000K

LAMPING

Source	Linear LED
Total power	251W
Emission	Diffused orientable
Switching	DALI 1-100%
Tension	220/240V
Color temperature	4000K
Luminous flux	17072lm
Typ CRI	90
Energy class	A+
IP class	40
Dimensions	350x150x5cm
Materials	Aluminium
Notes	included: 2 drivers WALIM150W24VIN, 2x dimmer interface WDIMDALIHP, 4x electrical cables 5m, 6x adjustable metal cables length 3m (including ceiling attachment). Shipped in 4 pieces
Customization options	Shapes, sizes
Accessories	Canopy, for concrete ceiling Ceiling plate, for false ceiling
Net lamp weight	9,9 kg

Codes

BZRO17B35G15NBO
BZRO17B35G15NNE
BZRO17B35G15NOR


Structure

white
black
gold

PACKAGE

Package 01 Dimension: 210x110x15 cm / Gross weight: 15,3 kg

Certificazioni



4X2M | DOWNLIGHT - 2700K

LAMPING

Source	Linear LED
Total power	148W
Emission	Diffused orientable
Switching	DALI 1-100%
Tension	220/240V
Color temperature	2700K
Luminous flux	8536lm
Typ CRI	90
Energy class	A+
IP class	40
Dimensions	400x200x5cm
Materials	Aluminium
Notes	included: 1 driver WALIM250W24VIN, 1 dimmer interface WDIMDALIHP, 4x electrical cables 5m, 6x adjustable metal cables length 3m (including ceiling attachment). Shipped in 4 pieces
Customization options	Shapes, sizes
Accessories	Canopy, for concrete ceiling Ceiling plate, for false ceiling
Net lamp weight	11,4 kg

Codes

BZRO16C40G15DBO
BZRO16C40G15DNE
BZRO16C40G15DOR


Structure

white
black
gold

PACKAGE

Package 01 Dimension: 210x110x15 cm / Gross weight: 16,8 kg

Certificazioni



4X2M | UP - DOWNLIGHT - 2700K

LAMPING

Source	Linear LED
Total power	296W
Emission	Diffused orientable
Switching	DALI 1-100%
Tension	220/240V
Color temperature	2700K
Luminous flux	17126lm
Typ CRI	90
Energy class	A+
IP class	40
Dimensions	400x200x5cm
Materials	Aluminium
Notes	included: 2 driver2 WALIM150W24VIN, 2x dimmer interface WDIMDALIHP, 4x electrical cables 5m, 6x adjustable metal cables length 3m (including ceiling attachment). Shipped in 4 pieces
Customization options	Shapes, sizes
Accessories	Canopy, for concrete ceiling Ceiling plate, for false ceiling
Net lamp weight	12,2 kg

Codes

BZRO17C40G15DBO
BZRO17C40G15DNE
BZRO17C40G15DOR


Structure

white
black
gold

PACKAGE

Package 01 Dimension: 210x110x15 cm / Gross weight: 17,6 kg

Certificazioni



4X2M | DOWNLIGHT - 3000K

LAMPING

Source	Linear LED
Total power	148W
Emission	Diffused orientable
Switching	DALI 1-100%
Tension	220/240V
Color temperature	3000K
Luminous flux	9067lm
Typ CRI	90
Energy class	A+
IP class	40
Dimensions	400x200x5cm
Materials	Aluminium
Notes	included: 1 driver WALIM250W24VIN, 1 dimmer interface WDIMDALIHP, 4x electrical cables 5m, 6x adjustable metal cables length 3m (including ceiling attachment). Shipped in 4 pieces
Customization options	Shapes, sizes
Accessories	Canopy, for concrete ceiling Ceiling plate, for false ceiling
Net lamp weight	11,4 kg

Codes

BZRO16C40G15WBO
BZRO16C40G15WNE
BZRO16C40G15WOR


Structure

white
black
gold

PACKAGE

Package 01 Dimension: 210x110x15 cm / Gross weight: 16,8 kg

Certificazioni



4X2M | UP - DOWNLIGHT - 3000K

LAMPING

Source	Linear LED
Total power	296W
Emission	Diffused orientable
Switching	DALI 1-100%
Tension	220/240V
Color temperature	3000K
Luminous flux	18134lm
Typ CRI	90
Energy class	A+
IP class	40
Dimensions	400x200x5cm
Materials	Aluminium
Notes	included: 2 drivers WALIM150W24VIN, 2x dimmer interface WDIMDALIHP, 4x electrical cables 5m, 6x adjustable metal cables length 3m (including ceiling attachment). Shipped in 4 pieces
Customization options	Shapes, sizes
Accessories	Canopy, for concrete ceiling Ceiling plate, for false ceiling
Net lamp weight	12,2 kg

Codes

BZRO17C40G15WBO
BZRO17C40G15WNE
BZRO17C40G15WOR


Structure

white
black
gold

PACKAGE

Package 01 Dimension: 210x110x15 cm / Gross weight: 17,6 kg

Certificazioni



4X2M | DOWNLIGHT - 4000K

LAMPING

Source	Linear LED
Total power	148W
Emission	Diffused orientable
Switching	DALI 1-100%
Tension	220/240V
Color temperature	4000K
Luminous flux	10074lm
Typ CRI	90
Energy class	A+
IP class	40
Dimensions	400x200x5cm
Materials	Aluminium
Notes	included: 1 driver WALIM250W24VIN, 1 dimmer interface WDIMDALIHP, 4x electrical cables 5m, 6x adjustable metal cables length 3m (including ceiling attachment). Shipped in 4 pieces
Customization options	Shapes, sizes
Accessories	Canopy, for concrete ceiling Ceiling plate, for false ceiling
Net lamp weight	11,4 kg

Codes

BZRO16C40G15NBO
BZRO16C40G15NNE
BZRO16C40G15NOR


Structure

white
black
gold

PACKAGE

Package 01 Dimension: 210x110x15 cm / Gross weight: 16,8 kg

Certificazioni



4X2M | UP - DOWNLIGHT - 4000K

LAMPING

Source	Linear LED
Total power	296W
Emission	Diffused orientable
Switching	DALI 1-100V
Tension	220/240V
Color temperature	4000K
Luminous flux	20149lm
Typ CRI	90
Energy class	A+
IP class	40
Dimensions	400x200x5cm
Materials	Aluminium
Notes	included: 2 drivers WALIM150W24VIN, 2x dimmer interface WDIMDALIHP, 4x electrical cables 5m, 6x adjustable metal cables length 3m (including ceiling attachment). Shipped in 4 pieces
Customization options	Shapes, sizes
Accessories	Canopy, for concrete ceiling Ceiling plate, for false ceiling
Net lamp weight	12,2 kg

Codes

BZRO17C40G15NBO
BZRO17C40G15NNE
BZRO17C40G15NOR

Structure

white
black
gold

PACKAGE

Package 01 Dimension: 210x110x15 cm / Gross weight: 17,6 kg

Certificazioni

