



OBIN ON 92724 DIM5 B

30511 9225 B

AVAILABLE IN

BLACK 30511 9225 B



BRUSHED GREY 30511 9225 BRA

BRUSHED ANTHRACITE 30511 9225 BRAT

BRUSHED GOLD 30511 9225 BRG

BRUSHED OLD BRONZE 30511 9225 BROB

WHITE 30511 9225 W



 [View on website](#)

General info

LOCATION	indoor
INSTALLATION	Ceiling Surface mounted
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.6
ADJUSTABILITY	0° to 45° swiveling, 360° rotatable
INFORMATION	LENS FL-24° INCL.DIMMABLE POWER SUPPLY

Electrical info

ELECTRICAL	120-240V / 50-60Hz
CLASS	I
POWER SUPPLY INCLUDED	YES
DIM TYPE	DALI
ENERGY CLASS	E

Lightsource info

Lightsource Name	LED
Lightsource	LED array 11,6W / CRI>90 (R9: 60) / 2700K / 1458lm
TM-30 Values	Rf: 89 / Rg: 100
SDCM	SDCM1
Riskgroup	RG1
LM80	L90B10 > 50000
LED Technics (light source)	1458lm // 11,6W // 125lm/W
LED Technics (luminaire)	1217lm // 13W // 91lm/W

Requirements

SPY 90 TUBE

Accessories

HONEYCOMB 75


OBIN ON 92724 DIM5 B

30511 9225 B

For detailed installation instructions, please consult the manual: [30511_XXX5_HAND.pdf](#)


FINISH YOUR SPECIFICATION

Light altering devices



19810 0110 B HONEYCOMB 75 SINGLE USE B

Finish your product



19810 0170 B SPY 90 TUBE B

19810 0170 DC SPY 90 TUBE DC

19810 0170 FBR SPY 90 TUBE FBR

19810 0170 FG SPY 90 TUBE FG

19810 0170 GC SPY 90 TUBE GC

19810 0170 W SPY 90 TUBE W

Notes: